



AQUAPANEL®

07/2014

## AQUAPANEL® Joint Filler - grey

Cement-bound joint filler

Be certain,  
choose **AQUAPANEL®**

**AQUAPANEL®**



## Application

AQUAPANEL® Joint Filler – grey is a cement-bound filling material for full-surface skim coating of joints by hand. The joints are reinforced with AQUAPANEL® Joint Filler – grey and AQUAPANEL® Tape (10 cm).

As a joint filler, the product is suitable for use with AQUAPANEL® Cement Board Indoor (ceiling) and AQUAPANEL® Cement Board Outdoor (wall and ceiling).

## Base/pre-treatment

AQUAPANEL® Cement Board panels must be dry, clean and dust-free and fixed firmly on to a substructure.

## Mixing

Stir 20 kg AQUAPANEL® Joint Filler – grey into approx. 6.8 l of cold, clean water (0.34 l water/kg AQUAPANEL® Joint Filler - grey). We recommend the use of a 600 rpm stirring machine. Use a clean mixing container and mixing tool.

## Handling/installation

Tools: Float/smoothing trowel.

Fill joints, place AQUAPANEL® Tape (10 cm) and press in with a trowel. Allow the previous coating to dry or harden before applying another coat if required. Also cover the screwheads etc.

Clean tools and equipment immediately after use with water.

## Material coverage

■ Joints: approx. 0.7 kg/m<sup>2</sup>

## Working time

The material begins to harden approx. 45 minutes after stirring. Dirty mixing containers and tools, and high temperatures or wind can shorten the working time. Do not use the material once it begins to stiffen.

Wall joint: approx. 12 minutes/m<sup>2</sup> (incl. installation, screws and laying the joint tape – AQUAPANEL® Cement Board Outdoor only).

Ceiling joint: approx. 18 minutes/m<sup>2</sup> (incl. installation, screws and laying the joint tape).

## Working temperature/climate

AQUAPANEL® Joint Filler – grey should only be applied to AQUAPANEL® Cement Board panels once they have acclimatised to the ambient climatic conditions. The material, ambient and back- ground temperature must not fall below +5°C.

## Method of delivery/storage

- 20 kg/bag
- Store bags in the dry. Place the contents of damaged bags into a container and use first.
- Unopened storage life approx. 12 months

Item code: 131094

**AQUAPANEL®**

▶ [www.AQUAPANEL.com](http://www.AQUAPANEL.com)

@ [info@AQUAPANEL.com](mailto:info@AQUAPANEL.com)

© 2014 EN-07/14

AQUAPANEL® is a technologically advanced building system. Because it's a system, it involves clear step-by-step process from design idea to project completion. AQUAPANEL® cement board panels, accessories and services work in unison – you can be certain that your project will all come together as planned.

AQUAPANEL® is a registered trademark.

Knauf USG Systems GmbH & Co. KG, Zur Helle 11, 58638 Iserlohn, Germany

All technical changes reserved. Only the current printed instructions are valid. Our warranty is expressly limited to our products in flawless condition. The constructional and structural properties and characteristic building physics of Knauf systems can solely be ensured with the exclusive use of Knauf system components, or other products expressly recommended by Knauf. All application quantities and delivery amounts are based on empirical data that are not easily transferable to other deviating areas. All rights reserved. All amendments, reprints and photocopies, including those of excerpts, require the express permission of Knauf USG Systems GmbH & Co. KG, Zur Helle 11, 58638 Iserlohn, Germany.